

Amendments to the Specification

IN THE WRITTEN DESCRIPTION

Please replace the paragraph beginning at page 5, line 27, with the following rewritten paragraph:

Fig. 1 shows the holding device 1 in a cross-sectional view. The holding device comprises a shuttering device 2, which is preferably made of steel and has a U-shaped cross-section. This U-shaped cross-section can be easily seen in Figure 3~~Figure 2~~ and is formed by a cover wall 3 and legs 4 adjoining at both sides and extending in parallel. The shuttering device 2 rests on a surface 6 of a shuttering support 7 with supporting surfaces 5. The shuttering support 7 is preferably made of steel and is preferably part of a shuttering table.

Please replace the paragraph beginning at page 6, line 17, with the following rewritten paragraph:

Furthermore, the magnet comprises a support device 13 securely connected to the magnet and having a stop 14. The stop can be engaged with the cover wall 3 of the shuttering device 2. In the representation according to Figure 1, the stop 14~~stop 4~~, however, is not engaged with the cover wall. Such an engagement is only effected if the magnet projects with respect to the supporting surfaces 5 of the shuttering device 2. Here, an angle of rotation of approx. 3° to 5° with respect to the position represented in Figure 1 is sufficient. The stop 14 is then engaged with the cover wall 3 or is supported at the same, respectively.